

Law Offices
BLOOSTON, MORDKOFKY, DICKENS, DUFFY & PRENDERGAST

2120 L STREET, NW
WASHINGTON, DC 20037

(202) 659-0830
FACSIMILE: (202) 828-5568

HAROLD MORDKOFKY
BENJAMIN H. DICKENS, JR.
JOHN A. PRENDERGAST
GERARD J. DUFFY
RICHARD D. RUBINO
MARY J. SISAK
D. CARY MITCHELL

ARTHUR BLOOSTON
1914 – 1999

AFFILIATED SOUTH AMERICAN OFFICES

ESTUDIO JAUREGUI & ASSOCIATES
BUENOS AIRES, ARGENTINA

ROBERT M. JACKSON
OF COUNSEL

PERRY W. WOOFER
LEGISLATIVE CONSULTANT

EUGENE MALISZEWSKYJ
DIRECTOR OF ENGINEERING
PRIVATE RADIO

December 8, 2005

Via Electronic Submission

Marlene H. Dortch, Secretary
Federal Communications Commission
445 12th Street, SW, Room TW-A325
Washington, DC 20554

Re: *Ex Parte* Presentation,

E911 Requirements for IP-Enabled Service Providers- WC Docket No. 05-196
Consumer Protection in the Broadband Era- WC Docket No. 05-271

Dear Ms. Dortch:

On behalf of the Alarm Industry Communications Committee (AICC), Lou Fiore, Bob Bonifas, Bill Signer and I met with Scott Bergmann, Legal Advisor to Commissioner Adelstein, on December 7, 2005, to discuss the alarm industry's concerns with voice over internet protocol (VoIP) services and the comments filed by the Central Station Alarm Association and AICC in the FCC's ongoing proceeding concerning the provision of E911 capability by VoIP providers. In the E911 VoIP proceeding, the alarm industry asked the FCC to impose notification and non-interference requirements on VoIP providers to protect the safety interests of subscribers to central station alarm services. Information concerning notification that was provided at the meeting is attached hereto.

In the meeting, AICC stated that to be compatible with alarm service, VoIP providers must:

1. Pass alarm communicator signals undistorted.
2. Ensure line seizure is not compromised.
3. Provide the ability for alarm control panels to "see" a telephone line equivalent (voltage and dialtone).
4. Provide sufficient battery backup for VoIP and cable hardware.

AICC explained that the alarm industry must meet certain battery backup requirements in connection with fire alarm services and that VoIP services currently are not compatible with these requirements.

Pursuant to Section 1.1206 of the Commission's rules, this letter is being electronically filed with your office. Please associate this letter with the files in the above-referenced proceedings.

Sincerely,

_____/s/_____
Mary J. Sisak

cc: Scott Bergmann

A VoIP service provider shall provide clear and conspicuous notice to each customer prior to installation and/or number activation of VoIP service that to ensure proper functioning of alarm and security system monitoring services:

1. the customer's alarm or security system must be tested and the alarm or security provider must be notified after VoIP service is installed; and
2. in order for alarm and security system signaling to function in the event of a power outage, twenty-four hour battery backup is required for equipment installed in connection with the VoIP service.

Equipment sold or provided which is necessary to connect VoIP service shall contain a clear and conspicuous warning that to ensure proper functioning of alarm and security system monitoring services:

1. the customer's alarm or security system must be tested and the alarm or security provider must be notified when VoIP service is installed; and
2. in order for alarm and security system signaling to function in the event of a power outage, twenty-four hour battery backup is required for equipment installed in connection with the VoIP service.